

AXLES

Customer Name												
Beam Only (With Springs)			Beam Only (No Springs)			Axle Beam Round Diameter:						
						2K = 1-3/4"		3.5K = 2-3/8"		3.5K=3" (Special Order)		
						5.2 - 7K = 3"		8K = 3"		10K = 4" or 5"		
						12K/16K = 5"						
Customer Part Number												
Model #	2K	3.5K	4.4K	5.2K	6K	7K	8K	8K HYB	10K	12K	16K	
Axle Capacity												
Spindle Style												
Straight						4" Drop (Up to 8K)						
Lubrication Type (if grs)												
Solid Cup Standard						Super Lube/Zerk						
Fluid Type												
Oil						Grease						
Axle Type												
Brake						Idler						
Brake Type												
Disc		Hydraulic		Electric		Electric, Self Adjust			Electric, Self Adjust ABS			
Air (12-16K)		Air (12-16K)		Air (12K-16) ABS								
Brake Flange, Opt on 2K & 3.5K												
Yes						No						
Tube Type												
Standard						Heavy Wall						
Camber												
Yes						No (Not Recommended)						
Bolt Pattern												
Brake		475	545	550	555	655	865	8/275mm				
Idler		440	475	545 (2K - 5.5")		545 (2K/4.4K - 6.5")		550	555	655	865	
Stud Size												
1/2"			5/8"		9/16"		M22					
Hub Face Dimension						Spring Center Dimension						See Below
Spring Orientation												
Overslung						Underslung						
Spring Seat 10K-16K												
Fixed						Adjustable			Hutch Style			
Spring Type												
Double Eye				Slipper		HDSS DBL Slipper			No Springs			
Spring Length, Eye to Eye No Load												
20"		23"		25"		Other (Specify)						
Tube Coating												
Powder Coat Black						Raw						

